

Sulux616 Handheld / Sulux616A Handfree Barcode Scanner



Scan Mode	Sulux616	handheld, manual, without auto sensor
	Sulux616A	handfree, automatic & manual, with auto sensor
CPU	32 bits	
Decoding Rate	100 times/second	
Scan Precision	3mil	
Scan Width	30mm@scan window, 220mm@200mm	
Scan Depth of Field	0-350mm (0.33mm PCS 0.9)	
Support Interface	RS232, PS2 and USB	
Material	ABS + PC	
Cable	Standard 2M straight	
Laser Class	Meet the Grade I National Criteria for Laser Safety	
Certificate	CE	
Packing	Sulux616	20pcs/carton, carton size: 56×26×38cm 50pcs/carton, carton size: 57×51×47cm
	Sulux616A	12pcs/carton, carton size: 46×45×44cm 24pcs/carton, carton size: 61×43×63cm

XL 2020 Omnidirectional Barcode Scanner



Scan Mode	Omnidirectional and single line scan
Laser Lines	20 laser lines, 5 directions of 4 parallel lines
Scan Speed	1500 times/second
Light Source	Visible Laser Diode 650nm
Depth of Field	0-200mm for 0.33mm UPC/EAN 100%
Support Interface	USB, RS232, PS/2
Visual Indicators	Two color LED (blue & red)
Beeper Operation	Programmable tone & volume
Size	L x W x H: 105mm x 100mm x 156mm
Weight	300g
Material	ABS+PC
Cable	Standard 2M straight
Voltage	5V
Laser Class	Meet the Grade 1 National Criteria for Laser Safety
Certificate	CE, RoHS